



CBSW4-S



Main features:

Voltage, current and charging profile configurable with smart cards (provided separately)

Power from 480W up to 2160W

Voltage 12V, 24V, 36V and 48V

Current from 40A to 60A

DIMENSIONS (LxWxH): 485x505x245 mm

19.09x19.88x9.65 in

WEIGHT: 36,40-49 Kg – 80.25-108 lbs

PROTECTION GRADE IP20

INPUT VOLTAGE: 240 Vac – 50-60 Hz



Battery Voltage	Battery Range		Charging Current	Model
	5h	20h		
12V	300 + 360 Ah	370 + 450 Ah	40A	12-40
	360 + 440 Ah	420 + 540 Ah	50A	12-50
	450 + 550 Ah	560 + 650 Ah	60A	12-60
24V	300 + 360 Ah	370 + 450 Ah	40A	24-40
	360 + 440 Ah	420 + 540 Ah	50A	24-50
	450 + 550 Ah	560 + 650 Ah	60A	24-60
36V	260 + 320 Ah	340 + 425 Ah	30A	36-30
	300 + 360 Ah	370 + 450 Ah	40A	36-40
	360 + 440 Ah	420 + 540 Ah	50A	36-50
48V	450 + 550 Ah	505 + 675 Ah	60A	36-60
	285 + 360 Ah	335 + 450 Ah	40A	48-40

