



# GREEN8



### Main features:

- Modular system (4 configurable modules)
- Power up to 10.5 kW, up to 200A @ 48V, up to 130A @ 80V, up to 100A @ 96V
- Programmable via USB type A/B port or via display
- Graphical display

**DIMENSIONS (LxWxH):** 448x665,50x217,50 mm  
19.45x26.20x8.5 in.

**WEIGHT:** 43,35 Kg - 95.5 lbs

**PROTECTION GRADE** IP20

**INPUT VOLTAGE:** 200/208-240/400/480/600 Vac – 50-60 Hz

Battery Voltage	IUIa Wet 8h Range (C5)	IUIa Wet 12h Range (C5)	IUIa Gel PzV 10-14h Range (C5)	Charging Current	Model
24V	900 + 1100 Ah	1440 + 1760 Ah	1110 + 1350 Ah	160A	24-160
	1010 + 1240 Ah	1620 + 1980 Ah	1250 + 1520 Ah	180A	24-180
	1130 + 1380 Ah	1800 + 2200 Ah	1380 + 1690 Ah	200A	24-200
36V	900 + 1100 Ah	1440 + 1760 Ah	1110 + 1350 Ah	160A	36-160
	1010 + 1240 Ah	1620 + 1980 Ah	1250 + 1520 Ah	180A	36-180
	1130 + 1380 Ah	1800 + 2200 Ah	1380 + 1690 Ah	200A	36-200
48V	900 + 1100 Ah	1440 + 1760 Ah	1110 + 1350 Ah	160A	48-160
	1010 + 1240 Ah	1620 + 1980 Ah	1250 + 1520 Ah	180A	48-180
	1130 + 1380 Ah	1800 + 2200 Ah	1380 + 1690 Ah	200A	48-200
72V	620 + 760 Ah	990 + 1210 Ah	760 + 930 Ah	110A	72-110
	680 + 830 Ah	1080 + 1320 Ah	830 + 1020 Ah	120A	72-120
	730 + 890 Ah	1170 + 1430 Ah	900 + 1100 Ah	130A	72-130
80V	620 + 760 Ah	990 + 1210 Ah	760 + 930 Ah	110A	80-110
	680 + 830 Ah	1080 + 1320 Ah	830 + 1020 Ah	120A	80-120
	730 + 890 Ah	1170 + 1430 Ah	900 + 1100 Ah	130A	80-130
96V	450 + 550 Ah	720 + 880 Ah	550 + 680 Ah	80A	96-80
	560 + 690 Ah	900 + 1100 Ah	690 + 850 Ah	100A	96-100

